



STYLE SPECIFICATION SHEET

STYLE NAME:	Patriot
YARN #1 TYPE:	Polytex USA MFPE300BO
COLOR:	Field Green, FG/Olive, & FG/Lime
TOTAL DENIER:	Approx 9450 (1575x6)
DESCRIPTION:	Proprietary PE formulation for superior wear resistance
THICKNESS/FORM:	Approx. 320 micron bow form
YARN #2 TYPE:	Polytex USA MFPE150RE texturized yarn
COLOR:	Field Green
TOTAL DENIER:	Approx 8100 (1350x6)
DESCRIPTION:	Proprietary PE formulation for superior wear resistance
THICKNESS/FORM:	Approx. 150 micron rectangular, rounded edge form
TOTAL YARN FACE WT:	69 Oz. / SqYd
PRIMARY BACKING #1:	13 pic polybac
PRIMARY BACKING #2:	18 pic polybac
PRIMARY BACKING WT:	7 Oz. / SqYd
SECONDARY COATING:	20 Oz. Urethane / SqYd
TOTAL PRODUCT WT:	96 Oz. / SqYd

TUFTING INFORMATION

PILE HEIGHT:	1 1/8" TUFTED
STITCH RATE:	AS REQUIRED
TUFTING GAUGE:	3/8"
ROLL WIDTHS:	15'
DRAINAGE PERFORATIONS:	STANDARD

These specifications are standard and may vary slightly due to manufacturing tolerances or consumer specifications.

*26 oz. Urethane is available as an option on production runs meeting our minimum requirements at a \$.07 / sq. ft. upcharge. 26 oz Urethane is necessary for material manufactured for FIELD applications.